



BANGLAMARK Multicrop Combine Harvester **BM-71**

120HP & Grain Tank 1500L



Address: Navana Sylvania
H#: KA-6/A Nadda Level-(3), Baridhara, Dhaka 1212.
Office: +8801977646434
E-mail: sales@banglamark.com.bd
Website: www.banglamark.com

Assemble Plant & Central Warehouse
Beraid, Badda, Dhaka
Bangladesh.



SPECIFICATION:

ITEM			PARAMETER
Brand			BANGLAMARK
Model			BM-52
Feeding Capacity		(kg/s)	3
Overall Dimension Length×Width×Heights		(mm)	5180×2585×2720
Weight		(kg)	3420
Productivity of Operating Hours		(hm ² /h)	0.27 ~0.96
Engine	Engine Model		4D35ZT32/1004
	Rated Power)	(kW/hp)	88KW/120HP(Alternative)
	Engine Type		Water-Cooled, 4-Cylinder, DI-Injection, Vertical Diesel.
	Rated Rotation Speed	(r/min)	2400
	Fuel consumption	(kg/hm ²)	28
Driving System	Type of Gearbox		Hydraulic type + HST(3F, 3R)
	Steering		Clutch and Brake.
	Type of Brake		By Foot.
Traveling System	Rubber Track	(mm)	500 x 90 x 51
	Gauge		1150
	Track ground pressure		24
	Theoretical Operating Speed	(km/h)	0.25~8.5
	Minimum Ground Clearance	(mm)	310
Cutting header	Height Adjustment		Hydraulics.
	Cutting Width (mm)	(mm)	2200
	Type of Blade		VI Type / Left and Right.
	Type of Header Auger		Telescopic Screw Conveying.
	Pickup Reel		Eccentric Tooth(off-centre), Diameter 944mm, Qty 5 pcs.
Threshing System	Threshing System		Spiked Tooth Axial Flow
	Threshing Cylinder Quantity		1
	Cylinder Diameter×Length	(mm)	φ626 x 2000
	Concave sieve		Grid type, 4 pcs
	Cleaning Mechanism Type		Air and Screen Cleaning, Vibrating Sieve adjustable
	Fan		Centrifugal Type, Diameter 395, Qty 1 pcs
Grain Storing	Automatic Unloading		Grain Tank Capacity 950L with 360° Unloading Auger

*Note: Single Threshing Drum & Double Threshing Drum are available with suitable hp based on customer demand.